


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/5/11	D.GRIFFIN
B	ECN 5665: REVISED FASTENER MATERIAL AND PANEL FINISH	8/16/11	D.FRISIELLO



RoHS Compliant ✓

NOTES:



MATERIAL, PANEL: .06 THICK COLD ROLLED STEEL.
MATERIAL, FASTENER: THERMOPLASTIC



FINISH: BLACK POWDER COAT.

COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0%	APPROVALS	DATE		45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	8/3/11		CATEGORY
ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 .XX = ± .02 .XXX = ± .005	CHECKED BY M.SEDLESKI	8/3/11	PRODUCT DESCRIPTION	
PROJECTION 	APPROVED BY M.MARTINEZ	8/3/11	SC SMP LX, MTRJ, LC DPLX FIBER SUB PANEL	
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		SIZE A	FSCM NO. 43321
	COLOR VARIATIONS MAY OCCUR		DWG. NO. FSP-SCMTLC-BNK	REV. B
			SCALE: NONE	CAD FILE: FSP-SCMTLC-BNK.SLDDRW
				SHEET 1 OF 1